

XSD Ultra[®]

Extra Severe Duty Motors

LV Induction Motor

Extra Severe Duty NEMA Premium Efficient 0.75-300 HP 230/460, 460, 575V











All Premium Efficient Motors Are Not Built the Same

Reliability is Built In

Purchasing dependable electric motors is an investment in the reliability of your operation; and system reliability means serious savings to your bottom line.

We've engineered motors to address all of the top factors that can shorten motor life:

Bearings

- Heat
- Stress
- Load
- Fatigue
- Vibration
- Misalignment
- Contamination
- Lubrication
- · Electrical discharge

Windings

- Heat
- Inverters
- · Voltage problems
- Load
- Contamination

Key Features


Five year warranty (60/66 months) is standard. This comprehensive warranty program covers both mechanical and NEMA Premium effiency performance.

ISO 1940 Grade 1.0 Precision Plus balance to 0.04 in/sec results in smooth, reliable operation and long bearing life.

Built for a long 130,000 hour L10 direct connected and 26,280 hour L10 belted bearing life without adjusting factors.

Complete test per MG1 Part 12 IEEE Standard 112, Test Method B on 2% of all production. Verification of compliance and routine test report supplied with every XSD Ultra motor.

Stock XSD Ultra motors can be UL listed, CSA listed, or GE self certified for Division 2 locations or modified to meet ATEX Zone 2 or CE requirements.





Embossed 316 stainless steel nameplate stamped with complete operational and maintenance information.

Charged lube system with Polyurea grease decreases the potential for contaminants in the lubricant.

Rigid and recessed severe-duty shaft slinger provides bearing system protection. Field modifiable to a noncontact rotating seal on the drive-end.

Temperature resistant Polyurea bearing grease suitable for temperatures of -40° to +120°.

Cast iron bearing cap with gasket retains lubricant and protects the interior of the motor and the bearing system from contaminants.

Stainless steel combination breather/ drains allow condensation to enscape

Fan covers (324-449
Frames) are secured with rugged axial mounting bolts.

Versatile dual mounting holes.


Rugged cast iron frame, conduit box and fan cover.

Oversized gasketed conduit box helps to keep moisture out.



GEGARD™ Insulation offers added protection

Our Class H GEGARD insulation system is designed to excel in variable frequency drive applications where lesser designs often short circuit and cause overcurrent trips.



Rotational Varnish Application

Even resin coverage. Less gaps (helps prevent corana inception damages).

Strong Bond

Wire bonding guards against end-turn vibration.

High Protection

Contaminants can't penetrate tightly bonded windings and slots.

Corrosion resistant and rugged SAE Grade 5 hardware.

Epoxyester paint system stands up to corrosive environments and meets the IEEE 841 paint equirements.

Finned end-shields (324-449 Frames) improve heat dissipation and extend bearing life.



Five point cast-in vibration probe mounting locations (four radial and one axial).









www.gemotorswolong.com